

ECHO™ PEDICURE CHAIR

Specifications

Dimensions: 61.71" L (157 cm) x 29.5" W (75 cm) x 52.5" H (133 cm)

From Floor to Seat: 24" (61 cm)

Shipping Dimensions (Carton Size): 75.0" L (190 cm) x 40.0" W (102 cm) x 44" H (112 cm)

Net Weight: 192 lbs (75 kg)

Shipping Weight without accessories: 310 lbs (141 kg)

Shipping Weight with accessories: 366 lbs (166 kg)

Client Weight Capacity: 350 lbs (160 kg)

Basin Capacity: 3.75 US Gallons (14.2 liters)

Power Requirements: 120V AC, 15 Amp, 60HZ. A separate and dedicated 15 Amp GFCI protected circuit MUST be used for each Echo Pedicure Chair.

Construction: Welded steel frame with veneered wood panels. ABS cover panels.

Basin: Highly chemical resistant ABS Plastic, pre-plumbed.

Jet System: One (1) Dual Jet Stream No Pipe™ Jet. Removable screen, no recirculating pipes. ON/OFF controlled by air-activated switch.

IMPORTANT: The Echo Pedicure Chair MUST be installed by a licensed electrician and a licensed plumber in accordance with all national, state and local codes/regulations.

PLUMBING

Incoming: Hot/Cold supply lines required (1/2" ID). Connections located on back of spa.

Sprayer/Filler: Inline back-flow prevention is provided.

Discharge: Gravity drain or optional factory installed drain pump. If factory installed drain pump is utilized, built-in back flow prevention is provided.

NOTE: If through floor installation is desired, refer to Plumbing Rough-in drawing (available at ContinuumFootspas.com). See Owners Manual for complete installation instructions.

Massage: Rolling and kneading Shiatsu back massage, built-in, commercial grade. Massage glides on vertical track or targets specific areas of the back. Controlled by durable hand held control wand.

Controls:

Armchair: Left Side: Seat Forward/Backward, and Recline. Electronically controlled.
Right Side: Handheld Control Wand for Shiatsu rolling/kneading massage.

All Controls are low voltage (12V)

Certification: Underwriters Laboratories Listed  US Compliance Listings to the following Standards:

UL 1951, CAN/CSA C22.2 No. 68-92,

ANSI/ASME A112.18.3M, A112.19.7M, A112.18.1, CSA B125.1.2005

Compliant with IAPMO Plumbing Standards. Fixtures and hoses are UPC compliant.

Compliant and approved in the State of Massachusetts.

Limited Warranty*: Jet: Dual Jet Stream No Pipe™ Jet - twenty four (24) months from shipment from Continuum Footspas facility.

Other components/parts - Twelve (12) months from shipment from Continuum Footspas facility.

Labor: Twelve (12) months labor may be covered under this Limited Warranty.

***See Limited Warranty for complete details**

ACCESSORIES:

Technician's chair: Base: 24" diameter (61 cm) Height range: (excluding cushion) 13.5" to 16" (34 cm to 41 cm) Net weight: 15 lbs (6.80 kg)

Shipping Dimensions: 30" W (76 cm) x 24" L (61 cm) x 12" H (31 cm) Shipping Weight: 23 lbs (11 kg)

Accessory Cart: 25" L (64 cm) x 18" W (46 cm) x 23" H (58 cm) Net Weight: 33 lbs (14.9 kg)

Shipping Dimensions: 30" W (76 cm) x 24" L (61 cm) x 12" H (31 cm) Shipping Weight: 35 lbs (16 kg)

Note: Due to continuous improvements, all specifications are subject to change without notice. All dimensions and weights are approximate.